

COMMERCIAL DRIVE TABLE 5

DUAL SERVICE DRIVEWAYS					
Design Features		Curbed Roadway		Uncurbed Roadway	
		Standard	Range	Standard	Range
Right Driveway Intersecting Angle	A	60 degrees	45 - 90 degrees	60 degrees	45 - 90 degrees
Right Driveway Entering Radius	C	15 ft.	5 - 50 ft.	20 ft.	5 - 50 ft.
Right Driveway Exiting Radius	D	10 ft.	5 - 25 ft.	5 ft.	5 - 25 ft.
Left Driveway Intersecting Angle	A	120 degrees	90 - 135 degrees	120 degrees	90 - 135 degrees
Left Driveway Entering Radius	C	10 ft.	5 - 25 ft.	5 ft.	5 - 25 ft.
Left Driveway Exiting Radius	D	15 ft.	5 - 50 ft.	20 ft.	5 - 50 ft.
Driveway Width	B	30 ft.	12 - 50 ft.	30 ft.	15 - 50 ft.
Distance Between Driveways	S	20 ft.	10 - 150 ft.	20 ft.	10 - 150 ft.
<p>The standard shall be used unless engineering judgment determines that another dimension within the range is more suitable for a particular site or a special condition is approved by the road commission.</p>					